46th St. 4600 N OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION $\frac{15}{7-23-01}$ TOWNSHIP $\frac{16}{9-25-06}$ RANGE $\frac{1}{9}$ DATE: 7-23-01-PARTY CHIEF: Wilcoxen Lu-i CREW: . 5500 TYPE OF MARKER: Horrison (no cap) METHOD OF ESTABLISHMENT: County: 11-10-96 ā IN. S.P.C. E ZONE NAD '83 16041502 509874.3810(m) NAME: N: E: 65097.4590(m) 6. tter 5. Lui 100 5450 212' astbourne Dr 224'+/-46th Street 4600 N 2.

Original post set 1820 by John Hendricks with witnesses: 30" sugar N 12 W 39 links; 18" beech S 13 E 15 links per Marion County Atlas pg. 11. Survey by O. W. Voorhis 4-10-1861 indicates a set rock w/brick bots underneath per Lawrence Township Legal Book pg. 22. Wilcoxen 12-18-75 called a brass plug in steel box. Greene 12-3-87 called the same. Kiste 8-21-96 called the same. Wilcoxen 11-10-96 called the same. Excavated by Wilcoxen 7-23-01 and brass plug in steel box was found 4" down. No other points were found. Harrison set.

16041502

REF.	DISTANCE	. DESCRIPTION	
1.	212'+/-	Due E to C/L of Ritter Ave 5500 E	
2,	43.18'	Mag nail w/brass washer W PwP#164-375 B	8"up
3.	131,70'	PK nail N PwP#167-371 B 4"up	
4.	224'+/-	Due W to C/L of Eastbourne Dr 5450 E	
5.	193.37	Top nut of fire hydrant	
6.	105.44'	NE corner of stone column	
7.	82.52	SE corner of stone column	
		4.	